

Diamond Coil

Customer:

Contact: Telephone:

Tel: +44 (0) 114 248 4391

Date: Job No:

Fax: +44 (0) 114 247 7663

Quote No: Notes:

Email: pfsales@preformed.co.uk

Serial No.: Manufacturer:

Insulation Class:

Voltage: Frame No.:

Hardcoil:

Amps: Frequency:

Softcoil:

RPM: Output:

Other:

1 Core Inside Dia:		13 No. of Conductors in Parallel:	24 Bracing Ring - Internal Diameter Back End:
2 Core Length:		14 Coil Pitch 1 -	25 Lead Position:
3 Finger Plate Width:		15 Weight of Insulated Coil:	26 Lead Position:
4 Number of Slots:	5 Number of Coils:	16 Connection End Coil Projection:	27 Wound Top - Left:
6 Total Slot Depth:		17 Back End Coil Projection:	28 Wound Top - Right:
7 Coil Space under Wedges:		18 Overall Coil Length:	29 Core to Top of Coil: Connection End:
8 Slot Width:		19 Coil Slot Length Top Leg:	30 Core to Bottom of Coil: Connection End:
9 Slot Skew Left Distance:		20 Coil Slot Length Bottom Leg:	31 Core to Top of Coil: Back End:
10 Slot Skew Right Distance:		21 Bracing Ring - Distance from Core Connection End:	32 Core to Bottom of Coil: Back End:
11 Turns per Coil:		22 Bracing Ring - Distance from Core Back End:	33 Turn Configuration Wide: Deep: other
12 Conductor Size - Width: Thickness:		23 Bracing Ring - Internal Diameter - Connection End:	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>

