

Armature Coil

Customer:

Tel: +44 (0) 114 248 4391 Fax: +44 (0) 114 247 7663

Email: pfsales@preformed.co.uk

Contact:

Telephone:

Date:

Motor Manufacturer:

Frequency:

HP/ KW / KVA:

Serial No.:

Frame No.:

Revs per Minute:

Insulation Class:

Hardcoil:

Softcoil:

Other:

Machine Voltage:

Machine Amps:

1	Core Inside Diameter:
2	Core Length:
3	Finger Plate Width:
4	Number of Slots:
5	Number of Coils
6	Total Slot Depth:
7	Coil Space under Wedge:
8	Slot Width:
9	Slot Skew Left Distance:
10	Slot Skew Right Distance:
11	Turns per Coil:
12	No. of Conductors in Parallel:
13	No. of Section
14	Copper Size - Width: Thickness:

15	Insulated Conductor Size - Width: Thickness:
16	Conductor Thickness in Commutator:
17	Riser Width:
18	Coil Width in Slot:
19	Coil Width outside Slot:
20	Straight Length of Coil Side:
21	Rear Extension:
22	Distance Between Core and Riser:
23	Coil Pitch: 1-
24	Leads Tinned or Not?:
25	Single or Double Knuckled - A: B:
26	Minimum Winding Diameter:
27	Front Extension:
28	Wiring Parallels Please Tick: <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> Other

